

REGISTRATION DATA DIRECTORY SERVICE (WHOIS) SPECIFICATION

1. **Registration Data Directory Services.** Until ICANN requires a different protocol, Registrar will operate a WHOIS service available via port 43 in accordance with RFC 3912, and a web-based Directory Service providing free public query-based access to at least the elements set forth in Section 3.3.1.1 through 3.3.1.8 of the Registrar Accreditation Agreement in the format set forth in Section 1.4 of this Specification. ICANN reserves the right to specify alternative formats and protocols, and upon such specification, the Registrar will implement such alternative specification as soon as reasonably practicable.

Following the publication by the IETF of a Proposed Standard, Draft Standard or Internet Standard and any revisions thereto (as specified in RFC 2026) relating to the web-based directory service as specified in the IETF Web Extensible Internet Registration Data Service working group, Registrar shall implement the directory service specified in any such standard (or any revision thereto) no later than 135 days after such implementation is requested by ICANN. Registrar shall implement internationalized registration data publication guidelines according to the specification published by ICANN following the work of the ICANN Internationalized Registration Data Working Group (IRD-WG) and its subsequent efforts, no later than 135 days after it is approved by the ICANN Board.

- 1.1. The format of responses shall follow a semi-free text format outline below, followed by a blank line and a legal disclaimer specifying the rights of Registrar, and of the user querying the database.
- 1.2. Each data object shall be represented as a set of key/value pairs, with lines beginning with keys, followed by a colon and a space as delimiters, followed by the value.
- 1.3. For fields where more than one value exists, multiple numbered key/value pairs with the same key shall be allowed (for example to list multiple name servers). The first key/value pair after a blank line should be considered the start of a new record, and should be considered as identifying that record, and is used to group data, such as hostnames and IP addresses, or a domain name and registrant information, together.

1.4. Domain Name Data:

1.4.1. **Query format:** `whois -h whois.example-registrar.tld EXAMPLE.TLD`

1.4.2. **Response format:**

The format of responses shall contain all the elements and follow a semi-free text format outline below. Additional data elements can be added at the end of the text

format outlined below. The data element may, at the option of Registrar, be followed by a blank line and a legal disclaimer specifying the rights of Registrar, and of the user querying the database (provided that any such legal disclaimer must be preceded by such blank line).

Domain Name: EXAMPLE.TLD
Registry Domain ID: D1234567-TLD
Registrar WHOIS Server: whois.example-registrar.tld
Registrar URL: http://www.example-registrar.tld
Updated Date: 2009-05-29T20:13:00Z
Creation Date: 2000-10-08T00:45:00Z
Registrar Registration Expiration Date: 2010-10-08T00:44:59Z
Registrar: EXAMPLE REGISTRAR LLC
Registrar IANA ID: 5555555
Registrar Abuse Contact Email: email@registrar.tld
Registrar Abuse Contact Phone: +1.1235551234
Reseller: EXAMPLE RESELLER¹
Domain Status: clientDeleteProhibited²
Domain Status: clientRenewProhibited
Domain Status: clientTransferProhibited
Registry Registrant ID: 5372808-ERL³
Registrant Name: EXAMPLE REGISTRANT⁴
Registrant Organization: EXAMPLE ORGANIZATION
Registrant Street: 123 EXAMPLE STREET
Registrant City: ANYTOWN
Registrant State/Province: AP⁵
Registrant Postal Code: A1A1A1⁶
Registrant Country: AA
Registrant Phone: +1.5555551212
Registrant Phone Ext: 1234⁷
Registrant Fax: +1.5555551213
Registrant Fax Ext: 4321
Registrant Email: EMAIL@EXAMPLE.TLD
Registry Admin ID: 5372809-ERL⁸

¹ Data element may be deleted, provided that if the data element is used, it must appear at this location.

² Note: all applicable statuses must be displayed in the Whois output.

³ May be left blank if not available from Registry.

⁴ For the Registrant, Admin and Tech contact fields requiring a "Name" or "Organization", the output must include either the name or organization (or both, if available).

⁵ All "State/Province" fields may be left blank if not available.

⁶ All "Postal Code" fields may be left blank if not available.

⁷ All "Phone Ext", "Fax" and "Fax Ext" fields may be left blank if not available.

⁸ May be left blank if not available from Registry.

Admin Name: EXAMPLE REGISTRANT ADMINISTRATIVE
Admin Organization: EXAMPLE REGISTRANT ORGANIZATION
Admin Street: 123 EXAMPLE STREET
Admin City: ANYTOWN
Admin State/Province: AP
Admin Postal Code: A1A1A1
Admin Country: AA
Admin Phone: +1.5555551212
Admin Phone Ext: 1234
Admin Fax: +1.5555551213
Admin Fax Ext: 1234
Admin Email: EMAIL@EXAMPLE.TLD
Registry Tech ID: 5372811-ERL⁹
Tech Name: EXAMPLE REGISTRANT TECHNICAL
Tech Organization: EXAMPLE REGISTRANT LLC
Tech Street: 123 EXAMPLE STREET
Tech City: ANYTOWN
Tech State/Province: AP
Tech Postal Code: A1A1A1
Tech Country: AA
Tech Phone: +1.1235551234
Tech Phone Ext: 1234
Tech Fax: +1.5555551213
Tech Fax Ext: 93
Tech Email: EMAIL@EXAMPLE.TLD
Name Server: NS01.EXAMPLE-REGISTRAR.TLD¹⁰
Name Server: NS02.EXAMPLE-REGISTRAR.TLD
DNSSEC: signedDelegation
URL of the ICANN WHOIS Data Problem Reporting System:
<http://wdprs.internic.net/>
>>> Last update of WHOIS database: 2009-05-29T20:15:00Z <<<

- 1.5. The format of the following data fields: domain status, individual and organizational names, address, street, city, state/province, postal code, country, telephone and fax numbers, email addresses, date and times must conform to the mappings specified in EPP RFCs 5730-5734 (or its successors), and IPv6 addresses format should conform to RFC 5952 (or its successor), so that the display of this information (or values returned in WHOIS responses) can be uniformly processed and understood.

2. Service Level Agreement for Registration Data Directory Services (RDDS)

2.1 Definitions

⁹ May be left blank if not available from Registry.

¹⁰ All associated nameservers must be listed.

- **IP address.** Refers to IPv4 or IPv6 addresses without making any distinction between the two. When there is need to make a distinction, IPv4 or IPv6 is used.
- **Probes.** Network hosts used to perform tests (see below) that are located at various global locations.
- **RDDS.** Registration Data Directory Services refers to the collective of WHOIS and Web based WHOIS services.
- **RTT.** Round-Trip Time or **RTT** refers to the time measured from the sending of the first bit of the first packet of the sequence of packets needed to make a request until the reception of the last bit of the last packet of the sequence needed to receive the response. If the client does not receive the whole sequence of packets needed to consider the response as received, the request will be considered unanswered.
- **SLR.** Service Level Requirement is the level of service expected for a certain parameter being measured in a Service Level Agreement (SLA).

2.2 Service Level Agreement Matrix

	Parameter	SLR (monthly basis)
RDDS	RDDS availability	less than or equal to 864 min of downtime
	RDDS query RTT	less than or equal to 4000 ms, for at least 95% of the queries
	RDDS update time	less than or equal to 60 min, for at least 95% of the probes

Registrar is encouraged to do maintenance for the different services at the times and dates of statistically lower traffic for each service. Since substantial downtime is already incorporated in the availability metric, planned outages or similar; any downtime, be it for maintenance or due to system failures, will be noted simply as downtime and counted for SLA purposes.

2.2.1 RDDS availability. Refers to the ability of all the RDDS services for the Registrar to respond to queries from an Internet user with appropriate data from the relevant registrar system. If 51% or more of the RDDS testing probes see any of the RDDS services as unavailable during a given time, the RDDS will be considered unavailable.

2.2.2 WHOIS query RTT. Refers to the **RTT** of the sequence of packets from the start of the TCP connection to its end, including the reception of the WHOIS response. If the **RTT** is 5-times or more the corresponding SLR, the **RTT** will be considered undefined.

2.2.3 Web-based-WHOIS query RTT. Refers to the **RTT** of the sequence of packets from the start of the TCP connection to its end, including the

reception of the HTTP response for only one HTTP request. If Registrar implements a multiple-step process to get to the information, only the last step shall be measured. If the **RTT** is 5-times or more the corresponding SLR, the **RTT** will be considered undefined.

- 2.2.4 RDDS query RTT.** Refers to the collective of “**WHOIS query RTT**” and “**Web-based- WHOIS query RTT**”.
- 2.2.5 RDDS update time.** Refers to the time measured from the receipt of an EPP confirmation to a transform command on a domain name, host or contact, up until the servers of the RDDS services reflect the changes made.
- 2.2.6 RDDS test.** Means one query sent to a particular “**IP address**” of one of the servers of one of the RDDS services. Queries shall be about existing objects in the registrar system and the responses must contain the corresponding information otherwise the query will be considered unanswered. Queries with an **RTT** 5 times higher than the corresponding SLR will be considered as unanswered. The possible results to an RDDS test are: a number in milliseconds corresponding to the **RTT** or undefined/unanswered.
- 2.2.7 Measuring RDDS parameters.** Every 5 minutes, RDDS probes will select one IP address from all the public-DNS registered “**IP addresses**” of the servers for each RDDS service of the Registrar being monitored and make an “**RDDS test**” to each one. If an “**RDDS test**” result is undefined/unanswered, the corresponding RDDS service will be considered as unavailable from that probe until it is time to make a new test.
- 2.2.8 Collating the results from RDDS probes.** The minimum number of active testing probes to consider a measurement valid is 10 at any given measurement period, otherwise the measurements will be discarded and will be considered inconclusive; during this situation no fault will be flagged against the SLRs.
- 2.2.9 Placement of RDDS probes.** Probes for measuring RDDS parameters shall be placed inside the networks with the most users across the different geographic regions; care shall be taken not to deploy probes behind high propagation-delay links, such as satellite links.

2.3 Covenants of Performance Measurement

Registrar shall not interfere with measurement **Probes**, including any form of preferential treatment of the requests for the monitored services. Registrar shall respond to the measurement tests described in this Specification as it would do with any other request from Internet users (for RDDS).